



AERO AVX 1000 2T

100% synthetic oil for 2-stroke light aircraft engines

USES

100% synthetic oil specifically developed to meet the requirements of the leading manufacturers of light aircraft engines.

Particularly suitable for 2-stroke injection and carburettor engines, including those used under severe service conditions (racing, training, banner towing, etc.).

Specifications:

API TC
JASO FD
ISO-L-EGD

MAIN PHYSICAL DATA

		Methods	Units	Values
Density at	20°C	ASTM D1298	kg/m ³	877
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	80
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	12
Viscosity index		ASTM D2270		145
Pour point		ASTM D97	°C	-51
Cleveland Open Cup Flash Point		ASTM D92	°C	112
Colour				Blue

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Synthetic ester bases provide exceptional resistance to high temperatures, preventing engines from seizing.
- ▶ Prevents clogged exhaust pipes, ports and pistons.
- ▶ Suitable for separated and pre-mix lubrication.
- ▶ Very good anti-smoke performance.
- ▶ Low-ash formula, preventing the formation of deposits in the combustion chamber.
- ▶ Low pour point means it can be used at very low temperatures.
- ▶ Dyed blue.



facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

