



YACCO - SAE 10W-40

Semi-synthetic oil for gasoline and diesel engines

USES

Designed for gasoline and diesel engines in passenger cars and light commercial vehicles used under severe service conditions.

Compatible with LPG vehicles and/or those with catalytic converters.

Specifications:

ACEA A3/B4

API SL/CF



MAIN PHYSICAL DATA

		Methods	Units	10W40
Density at	20°C	ASTM D4052	kg/m ³	870
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	96
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	14.3
Viscosity index		ASTM D2270		154
Pour point		ASTM D97	°C	-30
Cleveland Open Cup Flash Point		ASTM D92	°C	220
Dynamic viscosity at	-25°C	ASTM D5293	mPa·s	6500
HTHS viscosity (150°C)		CEC L-036-90	mPa·s	3.7
Sulphated ash		ASTM D874	% mass	1.3
Total Base Number (TBN)		ASTM D2896	mgKOH/g	10

The data given in this table represents typical production values and should not be taken as specifications.



PROPERTIES & ADVANTAGES

- ▶ **Synthetic based** formula for **improved thermal resistance**, meaning outstanding lubrication, even under severe driving conditions.
- ▶ Good detergent/dispersant properties keep the engine clean.
- ▶ 10W-40 viscosity provides quick oil flow upon start-up.
- ▶ Prevents engine wear and corrosion.
- ▶ High viscosity index and excellent viscosity stability in service.

facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

