



EMBASE MARINE SAE 75W-90

Synthetic gear case oil

USES

Anti-emulsion gear case oil specifically developed for the lubrication of propeller cases on outboard motors.

Specifications:

API GL-5 & API GL-4

MAIN PHYSICAL DATA

		Methods	Units	Values
Density at	20°C	ASTM D4052	kg/m ³	870
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	83
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	15
Viscosity index		ASTM D2270		191
Pour point		ASTM D97	°C	-42
Cleveland Open Cup Flash Point		ASTM D92	°C	196

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Outstanding extreme-pressure properties.
- ▶ Exceptional anti-emulsion properties, allowing fast water/oil separation in the event of water getting into the oil.
- ▶ Very high shear stability maintains optimal oil viscosity in service.
- ▶ Increased protection against corrosion.
- ▶ SAE 75W90 viscosity ensures excellent lubrication at all temperatures.
- ▶ Good anti-wear and anti-foam properties extend the engine's service life.



 facebook.com/yaccosas

 twitter.com/yaccosas

 youtube.com

