



# AGRIPRO HF6

Fluid for transmissions and hydraulic systems

## USES

Lubrication of transmissions, hydraulic systems, clutches and wet brake systems on agricultural and construction equipment where the use of API GL-4 SAE 20W- 30 or SAE 80W is specified. Also suitable for automatic or hydrostatic transmissions, torque convertors, hydraulic systems, power steering, power take-off (PTO) with oil-immersed clutch where the manufacturer recommend the use of UTTO (Universal Tractor transmission Oil) or meeting one of the following specifications:

**Specifications:** API GL-4; FORD M2C 86B/86B; HM 68/100  
MASSEY FERGUSON CMS 1141/1135; NEW HOLLAND NH 420A  
RENAULT AGRICULTURE 180596/88-3\*

- Use only when RENAULT THFI fluid is recommended. When RENAULT GA 12 fluid is recommended, use AGRIPRO HJD (Renault tractors: ARES, CELTIS, New ARES, etc.)

Suitable for use in other manufacturers' equipment: Fiat, JCB, Komatsu, Manitou...



## MAIN PHYSICAL DATA

		Methods	Units	Values
Density at	20°C	ASTM D4052	kg/m <sup>3</sup>	885
Kinematic viscosity at	40°C	ASTM D445	mm <sup>2</sup> /s	83
Kinematic viscosity at	100°C	ASTM D445	mm <sup>2</sup> /s	10.5
Viscosity index		ASTM D2270		110
Pour point		ASTM D97	°C	-27
Cleveland Open Cup Flash Point		ASTM D92	°C	210

The data given in this table represents typical production values and should not be taken as specifications.

## PROPERTIES & ADVANTAGES

- ▶ Specific additive package preventing brake chatter.
- ▶ Good protection against rust and corrosion.
- ▶ Excellent anti-wear properties.
- ▶ Outstanding oxidation and shear resistance, providing very good stability in service.
- ▶ Good anti-foam properties.
- ▶ Good water demulsibility.



[facebook.com/yaccosas](https://facebook.com/yaccosas)

[twitter.com/yaccosas](https://twitter.com/yaccosas)

[youtube.com](https://youtube.com)

