

INBOARD 100 4T SAE 15W-40

Mineral oil for 4-stroke inboard & Sterndrive engines

USES

Mineral oil for 4-stroke diesel & gasoline inboard and sterndrive engines.

Suitable for leisure and professional fishing boats.

Good protection against corrosion. Keeps engine clean.

<u>Specifications</u>: ACEA E7 & ACEA A3/B4; API CI-4/SL; Global DHD-1 Caterpillar ECF-2/ECF-1a; Cummins 20076/77/78 Deutz DQC III-10; Man M 3275; MB 228.3 MTU Type 2; Volvo VDS-3 Baudouin Service B (fuel with max. 0.2% sulphur content)

MAIN PHYSICAL DATA

	Methods	Units	Values
Density at 20°C	ASTM D4052	kg/m3	877
Kinematic viscosity at 40°C	ASTM D445	mm²/s	100
Kinematic viscosity at 100°C	ASTM D445	mm²/s	14
Viscosity index	ASTM D2270		142
Pour point	ASTM D97	C°	-36
Cleveland Open Cup Flash Point	ASTM D92	°C	218
Dynamic viscosity at -20°C	ASTM D5293	mPa⋅s	6000
HTHS viscosity (150 °C)	CEC L-036-90	mPa⋅s	3.7
Sulphated ash	ASTM D874	% mass	1.4
Total Base Number (TBN)	ASTM D2896	mgKOH/g	11



The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ► Specific formula suitable for severe service conditions and high temperatures.
- ► Enhanced lubricating power provides excellent anti-wear protection and prevents cylinder wear.
- ► High resistance to oxidation allows long oil change intervals.
- ► Compatible with Tier 2 and Tier 3 engines with depollution systems (without DPF).

► Suitable for all gasoline and diesel engines with or without turbocharger.





Before using this oil, always check the manufacturer's technical requirements in the equipment's service manual.