



# BVX R 200 – SAE 75W-80

High-quality mineral oil for manual transmissions

## USES

Lubrication of manual transmissions and drive axles in passenger cars and light commercial vehicles where API GL-4/API GL-4+ with SAE 75W- 80 viscosity oil is recommended by the OEM.

BVX R 200 75W80 provides easier gear shifting in cold temperatures and improves fuel economy.

### Specifications:

API GL-4+

P.S.A Group (Peugeot, Citroën, DS Automobiles)



## MAIN PHYSICAL DATA

|                                | Methods    | Units              | 75W-80 |
|--------------------------------|------------|--------------------|--------|
| Density at 20°C                | ASTM D4052 | kg/m <sup>3</sup>  | 886    |
| Kinematic viscosity at 40°C    | ASTM D445  | mm <sup>2</sup> /s | 49     |
| Kinematic viscosity at 100°C   | ASTM D445  | mm <sup>2</sup> /s | 8.25   |
| Viscosity index                | ASTM D2270 |                    | 142    |
| Pour point                     | ASTM D97   | °C                 | -42    |
| Cleveland Open Cup Flash Point | ASTM D92   | °C                 | 208    |

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ High viscosity index for a mineral oil, **ensuring a protective lubricating film** is maintained at high and low temperatures alike.
- ▶ **Good thermal stability. Excellent lubrication** of gearbox components, even under severe driving conditions.
- ▶ Very good anti-wear and anti-corrosion properties.
- ▶ Improved anti-friction properties to improve gear shifting.



 [facebook.com/yaccosas](https://facebook.com/yaccosas)

 [twitter.com/yaccosas](https://twitter.com/yaccosas)

 [youtube.com](https://youtube.com)

