



LR - 18

Coolant for use in hot climates (-18°C)

USES

Made using monoethylene glycol, demineralised water and specific additives, this premixed coolant does not have to be mixed with water.

Ideal for use in hot climates.



MAIN PHYSICAL DATA

	Methods	Units	Values
Appearance	Visual		Limpid
Colour	Visual		yellow
Density at 20°C	ASTM D4052	kg/m ³	1048
Protection	ASTM D1177	°C	-18
pH	ASTM D1287		9.2
Reserve of alkalinity (pH 5.5)	ASTM D1121	ml	14

The data given in this table represents typical production values and should not be taken as specifications.



PROPERTIES & ADVANTAGES

- ▶ The concentration has more inhibitors to provide excellent protection against corrosion and rust.
- ▶ Good anti-foam and anti-scale properties.
- ▶ Improves heat dissipation and helps engine cooling.
- ▶ Prevents the formation of deposits in the cooling system
- ▶ Meets the requirements of ASTM D3306 & NFR 15601 standards (except in terms of pH).
- ▶ Frost protection up to -18°C.

PRECAUTIONS FOR USE

- ▶ Can ONLY be mixed with coolants of the same type.
- ▶ Harmful if ingested. Contains a bittering agent, in accordance with French Decree No. 95-326 of 20th March 1995.

facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

