



TRF V12

Chainsaw bar oil
ISO VG 320

USES

This oil has been **specifically** designed for **chainsaws** and especially powerful ones for professional use.

Also suitable for **machine tools** where **ISO VG 320** grade oil is required.

Our full range of chainsaw oils also includes:

- less viscous oils for use under less severe service conditions:
YACCO TRF V8 ISO VG 220 and YACCO TRF V6 ISO VG 150.
- YACCO TRF BIO ISO VG 150 biodegradable oil for maximum protection of the environment and environmentally sensitive areas.



MAIN PHYSICAL DATA

		Methods	Units	TRF V12
Density at	20°C	ASTM D4052	kg/m ³	890
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	320
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	24
Viscosity index		ASTM D2270		95
Pour point		ASTM D97	°C	-9
Cleveland Open Cup Flash Point		ASTM D92	°C	230
Appearance				Ropy
Colour				Uncolored

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Perfect lubrication to prevent metal-to-metal contact and decrease friction and heating.
- ▶ Very good adhesive properties and a specific viscosity grade mean an oil film is kept in place on metal parts.
- ▶ High viscosity (ISO VG 320 grade) suitable for intense use of professional equipment.
- ▶ Reduces oil consumption by decreasing dripping and spattering.
- ▶ Excellent miscibility with all mineral oils.



facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

