

PREVENTIF E85/E85 FUEL PREVENTIVE TREATMENT

Fuel additive

USES

E85 FUEL PREVENTIVE TREATMENT has been formulated to clean and protect the injection system of engines using E85 fuel or fuels containing ethanol.

Ethanol promotes condensation of water and causes corrosion, fouling and wear.

Regular use of E85 FUEL PREVENTIVE TREATMENT lubricates the injection system and improves its resistance to corrosion.

MAIN PHYSICAL DATA

	Method	Units	Values
Aspect	visual		limpid
Colour	visual		yellow
Density at 20°C	ASTM D4052	kg/m3	798

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- Removes carbon deposits, harmful gums and varnishes that can clog internal passages.
- Lubricates the injection system and prevents wear.

Improves the corrosion resistance of components in contact with ethanol.

Suitable for all types of gasoline engines, with or without a catalytic converter.

Helps to reduce fuel consumption.

INSTRUCTIONS FOR USE

- Pour one dose (250ml) in the tank (+/- 50L) before filling up.
- Add once or twice a year or every 5,000 to 10,000 kilometers, depending on vehicle usage.
- When the additive is poured into the tank, it must be consumed immediately. Avoid prolonged storage of the treated fuel.









Before using this fluid, always check the manufacturer's technical requirements in your car's service manual