



FORK FLUID 7.5W

FORK OIL

USES

Hydraulic fluid for upside down or cartridge forks. Tested under race conditions. Provides progressive and smooth operation of suspension.

Particularly recommended for SHOWA or WHITE POWER cartridge-type forks.

This fluid is part of our YACCO FORK FLUID product range.

For softer damping, use FORK FLUID 2.5W or 5W; for firmer damping, use FORK FLUID 10W, 15W or 20W.

MAIN PHYSICAL DATA

		Methods	Units	7.5W
Density at	20°C	ASTM D4052	kg/m ³	860
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	22
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	5
Viscosity index		ASTM D2270		163
Pour point		ASTM D97	°C	-39
Cleveland Open Cup Flash Point		ASTM D92	°C	185

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ High-shear resistance.
- ▶ Excellent anti-foam, anti-wear, anti-corrosive and anti-friction properties.
- ▶ Optimal damping over a wide temperature range and under all service conditions.
- ▶ Stay-in-grade viscosity maintains high fluid performance over the service life of the oil.
- ▶ Protects O-rings.
- ▶ Compatible with fork oil seals.

